

CAPITÓLIO

MODULE TYPE		CSST145
Thyristor Modules		$I_{TRMS} = 2x 300 A$ $I_{TAVM} = 2x 130 A$ $V_{RRM} = 800-2300 V$
VOLTAGE RATINGS MAXIMUM	LIMITS UNITS	
V_{DRM} Repetitive peak off-state voltage,	1600-2200 V	
V_{DSM} Non-repetitive peak off-state voltage,	1600-2200 V	
V_{RRM} Repetitive peak reverse voltage,	1600-2200 V	
V_{RSM} Non-repetitive peak reverse voltage	1700-2300V	

OTHER RATINGS MAXIMUM LIMITS UNITS

Symbol	Test Conditions	Maximum	Ratings
I_{FRMS}	$T_{VJ} = T_{VJM}$	300	A
I_{FAVM}	$T_C = 100^{\circ}C$; 180° sine	130	A
I_{FSM}	$T_{VJ} = 45^{\circ}C$; t = 10 ms (50 Hz), sine	4750	A
I_{FSM}	$V_R = 0$ t = 8.3 ms (60 Hz), sine	5080	A
I_{FSM}	$T_{VJ} = T_{VJM}$ t = 10 ms (50 Hz), sine	4230	A
I_{FSM}	$V_R = 0$ t = 8.3 ms (60 Hz), sine	4530	A
i_{2dt}	$T_{VJ} = 45^{\circ}C$ t = 10 ms (50 Hz), sine	113 000	A ² s
i_{2dt}	$V_R = 0$ t = 8.3 ms (60 Hz), sine	108 000	A ² s
i_{2dt}	$T_{VJ} = T_{VJM}$ t = 10 ms (50 Hz), sine	89 500	A ² s
i_{2dt}	$V_R = 0$ t = 8.3 ms (60 Hz), sine	86 200	A ² s
$(di/dt)_{cr}$	$T_{VJ} = T_{VJM}$ repetitive, $I_T = 500 A$ f = 50 Hz, $t_P = 200 \mu s$ $V_D = 2/3 V_{DRM}$	150 A/ μs	A/ μs
	$I_G = 0.45 A$ non repetitive, $I_T = I_{TAVM}$ $di_G/dt = 0.45 A/\mu s$	500 A/ μs	A/ μs
$(dv/dt)_{cr}$	$T_{VJ} = T_{VJM}$; $V_{DR} = 2/3 V_{DRM}$ $R_{GK} = \infty$; method 1	1000	V/ μs
P_{GM}	$T_{VJ} = T_{VJM}$ $t_P = 30 \mu s$	120	W
	$I_T = I_{TAVM}$ $t_P = 500 \mu s$	60 8	W W
P_{GAV}			
V_{RGM}		10	V
T_{VJ}	repetitive, $I_T = 250 A$	-40...+150	°C
T_{VJM}		125	°C
T_{stg}		-40...+150	°C
V_{ISOL}	50/60 Hz, RMS t = 1 min	3000	V~
V_{ISOL}	$I_{ISOL} = 1 mA$ t = 1 s	3600	V~
M_d	Mounting torque (M6)	2.25-2.75/20-25	Nm/lb.in.
M_d	Terminal connection torque (M6)	2.25-2.75/20-25	Nm/lb.in.
Weight	Typical including screws	125	g

CAPITÓLIO Comércio Representação Importação e Exportação Ltda.
 Al. dos Pamaris, 188 - Campo Belo - ☎ 04086.020 - S. Paulo - 📞 (011) 5090-4500 📠 (011) 5543.0736
 CGC. : 00.023.280 / 0001-53 I.E. : 114.102.283.115 E.mail : capitolio@capitoliosemic.com.br
 Visite nosso SITE : www.capitoliosemic.com.br

CAPITÓLIO

Dimensions in mm (1 mm = 0.0394")

